

CDx4HC173、CDx4HCT173 ハイスピード CMOS ロジック、クワッド D タイプ・フリップ・フロップ、3 ステート

1 特長

- 3 ステート・バッファ付き出力
- ゲート付き入力および出力イネーブル
- ファンアウト (全温度範囲にわたって)
 - 標準出力: 10 個の LSTTL 負荷
 - バス・ドライバ出力: 15 個の LSTTL 負荷
- 広い動作温度範囲: $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$
- 平衡な伝搬遅延と遷移時間
- LSTTL ロジック IC に比べて消費電力を大幅削減
- HC タイプ
 - 2V~6V で動作
 - 優れたノイズ耐性: V_{CC} の $N_{IL} = 30\%$ 、 $N_{IH} = 30\%$ ($V_{CC} = 5\text{V}$ 時)
- HCT タイプ
 - 4.5V~5.5V で動作
 - LSTTL 入力ロジックと直接互換、 $V_{IL} = 0.8\text{V}$ (最大値)、 $V_{IH} = 2\text{V}$ (最小値)
 - CMOS 入力互換、 V_{OL} 、 V_{OH} で $I_L \leq 1\mu\text{A}$


2 概要

CDx4HC173 と CDx4HCT173 は 4 つの独立した D タイプ・フリップ・フロップを内蔵し、共有クロック (CP)、リセット (MR)、データ・イネーブル ($\overline{E1}$ 、 $\overline{E2}$) ピンを備えています。

デバイス情報

| 部品番号 | パッケージ ⁽¹⁾ | 本体サイズ (公称) |
|---------------|----------------------|------------------|
| CD54HC173F | CDIP (16) | 21.34mm × 6.92mm |
| CD54HCT173F3A | CDIP (16) | 21.34mm × 6.92mm |
| CD74HC173E | PDIP (16) | 19.31mm × 6.35mm |
| CD74HCT173E | PDIP (16) | 19.31mm × 6.35mm |
| CD74HC173M | SOIC (16) | 9.90mm × 3.90mm |
| CD74HCT173M | SOIC (16) | 9.90mm × 3.90mm |
| CD74HC173PW | TSSOP (16) | 5.00mm × 4.40mm |

- (1) すべてのパッケージについては、このデータシートの末尾にある注文情報を参照してください。



機能ブロック図



Table of Contents

| | | | |
|---|----|--|----|
| 1 特長 | 1 | 7.2 Functional Block Diagram..... | 10 |
| 2 概要 | 1 | 7.3 Device Functional Modes..... | 11 |
| 3 Revision History | 2 | 8 Power Supply Recommendations | 12 |
| 4 Pin Configuration and Functions | 3 | 9 Layout | 12 |
| 5 Specifications | 4 | 9.1 Layout Guidelines..... | 12 |
| 5.1 Absolute Maximum Ratings | 4 | 10 Device and Documentation Support | 13 |
| 5.2 Recommended Operating Conditions..... | 4 | 10.1 Documentation Support..... | 13 |
| 5.3 Thermal Information..... | 4 | 10.2 Receiving Notification of Documentation Updates.. | 13 |
| 5.4 Electrical Characteristics..... | 5 | 10.3 サポート・リソース..... | 13 |
| 5.5 Switching Characteristics..... | 6 | 10.4 Trademarks..... | 13 |
| 5.6 Prerequisite For Switching Characteristics..... | 7 | 10.5 Electrostatic Discharge Caution..... | 13 |
| 6 Parameter Measurement Information | 8 | 10.6 Glossary..... | 13 |
| 7 Detailed Description | 10 | 11 Mechanical, Packaging, and Orderable Information | 13 |
| 7.1 Overview..... | 10 | | |

3 Revision History


資料番号末尾の英字は改訂を表しています。その改訂履歴は英語版に準じています。

Changes from Revision E (October 2003) to Revision F (March 2022)

Page

- 最新のデータシート規格を反映するように、文書全体にわたって表、図、相互参照の採番方法を更新..... 1

4 Pin Configuration and Functions



J, N, D, or PW Package
16-Pin CDIP, PDIP, SOIC, or TSSOP
Top View

5 Specifications

5.1 Absolute Maximum Ratings

Over operating free-air temperature range (unless otherwise noted)⁽¹⁾

| | | MIN | MAX | UNIT |
|------------------|--|---|-----|--------|
| V _{CC} | Supply voltage | -0.5 | 7 | V |
| I _{IK} | Input diode current ⁽²⁾ | V _I < -0.5 V or V _I > V _{CC} + 0.5 V | | ±20 mA |
| I _{OK} | Output diode current ⁽²⁾ | V _O < -0.5 V or V _O > V _{CC} + 0.5 V | | ±20 mA |
| I _O | Output source or sink current per output pin | V _O > -0.5 V or V _O < V _{CC} + 0.5 V | | ±25 mA |
| | Continuous current through V _{CC} or GND | | ±70 | mA |
| T _J | Junction temperature | | 150 | °C |
| | Lead temperature (soldering 10s) (SOIC - lead tips only) | | 300 | °C |
| T _{stg} | Storage temperature | -65 | 150 | °C |

- (1) Stresses beyond those listed under *Absolute Maximum Rating* may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Condition*. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

5.2 Recommended Operating Conditions

| | | MIN | MAX | UNIT | |
|-----------------|--------------------------|------------------------|-----------------|------|----|
| V _{CC} | Supply voltage range | HC types | 2 | 6 | V |
| | | HCT types | 4.5 | 5.5 | |
| V _I | Input voltage | 0 | V _{CC} | V | |
| V _O | Output voltage | 0 | V _{CC} | V | |
| t _t | Input rise and fall time | V _{CC} = 2V | | 1000 | ns |
| | | V _{CC} = 4.5V | | 500 | |
| | | V _{CC} = 6V | | 400 | |
| T _A | Temperature range | -55 | 125 | °C | |

5.3 Thermal Information

| THERMAL METRIC | | N (PDIP) | D (SOIC) | NS (SOP) | PW (TSSOP) | UNIT |
|------------------|---|----------|----------|----------|------------|------|
| | | 16 PINS | 16 PINS | 16 PINS | 16 PINS | |
| R _{θJA} | Junction-to-ambient thermal resistance ⁽¹⁾ | 67 | 73 | 64 | 108 | °C/W |

- (1) For more information about traditional and new thermal metrics, see the [Semiconductor and IC Package Thermal Metrics](#) application report

5.4 Electrical Characteristics

| PARAMETER | | TEST CONDITIONS ⁽¹⁾ | V _{CC} | 25°C | | | -40°C to 85°C | | -55°C to 125°C | | UNIT |
|-------------------------------------|--|--------------------------------|-----------------|------|------|------|---------------|-------|----------------|-------|------|
| | | | | MIN | TYP | MAX | MIN | MAX | MIN | MAX | |
| HC TYPES | | | | | | | | | | | |
| V _{IH} | High-level input voltage | | 2 | 1.5 | | 1.5 | | 1.5 | | V | |
| | | | 4.5 | 3.15 | | 3.15 | | 3.15 | | V | |
| | | | 6 | 4.2 | | 4.2 | | 4.2 | | V | |
| V _{IL} | Low-level input voltage | | 2 | | 0.5 | | 0.5 | | 0.5 | V | |
| | | | 4.5 | | 1.35 | | 1.35 | | 1.35 | V | |
| | | | 6 | | 1.8 | | 1.8 | | 1.8 | V | |
| V _{OH} | High-level output voltage CMOS loads | I _{OH} = -20μA | 2 | 1.9 | | 1.9 | | 1.9 | | V | |
| | | I _{OH} = -20μA | 4.5 | 4.4 | | 4.4 | | 4.4 | | V | |
| | | I _{OH} = -20μA | 6 | 5.9 | | 5.9 | | 5.9 | | V | |
| | High-level output voltage TTL loads | I _{OH} = -6mA | 4.5 | 3.98 | | 3.84 | | 3.7 | | V | |
| | | I _{OH} = -7.8mA | 6 | 5.48 | | 5.34 | | 5.2 | | V | |
| V _{OL} | Low-level output voltage CMOS loads | I _{OL} = 20μA | 2 | | 0.1 | | 0.1 | | 0.1 | V | |
| | | I _{OL} = 20μA | 4.5 | | 0.1 | | 0.1 | | 0.1 | V | |
| | | I _{OL} = 20μA | 6 | | 0.1 | | 0.1 | | 0.1 | V | |
| | Low-level output voltage TTL loads | I _{OL} = 6mA | 4.5 | | 0.26 | | 0.33 | | 0.4 | V | |
| | | I _{OL} = 7.8mA | 6 | | 0.26 | | 0.33 | | 0.4 | V | |
| I _I | Input leakage current | V _{CC} or GND | 6 | | ±0.1 | | ±1 | | ±1 | μA | |
| I _{CC} | Supply current | V _{CC} or GND | 6 | | 8 | | 80 | | 160 | μA | |
| I _{OZ} | Three-state leakage current | | 6 | | ±0.5 | | ±0.5 | | ±10 | μA | |
| HCT TYPES | | | | | | | | | | | |
| V _{IH} | High-level input voltage | | 4.5 to 5.5 | 2 | | 2 | | 2 | | V | |
| V _{IL} | Low-level input voltage | | 4.5 to 5.5 | | 0.8 | | 0.8 | | 0.8 | V | |
| V _{OH} | High-level output voltage CMOS loads | I _{OH} = -20μA | 4.5 | 4.4 | | 4.4 | | 4.4 | | V | |
| | High-level output voltage TTL loads | I _{OH} = -6mA | 4.5 | 3.98 | | 3.84 | | 3.7 | | V | |
| V _{OL} | Low-level output voltage CMOS loads | I _{OL} = 20μA | 4.5 | | 0.1 | | 0.1 | | 0.1 | V | |
| | Low-level output voltage TTL loads | I _{OL} = 6mA | 4.5 | | 0.26 | | 0.33 | | 0.4 | V | |
| I _I | Input leakage current | V _{CC} and GND | 5.5 | | ±0.1 | | ±1 | | ±1 | μA | |
| I _{CC} | Supply Current | V _{CC} and GND | 5.5 | | 8 | | 80 | | 160 | μA | |
| ΔI _{CC} ^{(2) (3)} | Additional supply current per input pin | One of D0-D3 | 4.5 to 5.5 | | 15 | 54 | | 67.5 | | 73.5 | μA |
| | | One of E1 and E2 | 4.5 to 5.5 | | 15 | 54 | | 67.5 | | 73.5 | μA |
| | | CP | 4.5 to 5.5 | | 25 | 90 | | 112.5 | | 122.5 | μA |
| | | MR | 4.5 to 5.5 | | 20 | 72 | | 90 | | 98 | μA |
| | | One of OE1 and OE2 | 4.5 to 5.5 | | 50 | 180 | | 225 | | 245 | μA |

| PARAMETER | | TEST CONDITIONS ⁽¹⁾ | V _{CC} | 25°C | | | -40°C to 85°C | | -55°C to 125°C | | UNIT |
|-----------------|-----------------------------|--------------------------------|-----------------|------|-----|------|---------------|------|----------------|-----|------|
| | | | | MIN | TYP | MAX | MIN | MAX | MIN | MAX | |
| I _{OZ} | Three-state leakage current | | 5.5 | | | ±0.5 | | ±5.0 | | ±10 | µA |

- (1) V_I = V_{IH} or V_{IL}, unless otherwise noted.
- (2) For dual-supply systems theoretical worst case (V_I = 2.4 V, V_{CC} = 5.5 V) specification is 1.8 mA.
- (3) Inputs held at V_{CC} - 2.1.

5.5 Switching Characteristics

Input t_t = 6ns. Unless otherwise specified, C_L = 50pF

| PARAMETER | | V _{CC} (V) | 25°C | | -40°C to 85°C | -55°C to 125°C | UNIT |
|-------------------------|---|---------------------|-------------------|-----|---------------|----------------|------|
| | | | TYP | MAX | MAX | MAX | |
| HC TYPES | | | | | | | |
| t _{pd} | Propagation delay, clock to output | 2 | | 200 | 250 | 300 | ns |
| | | 4.5 | 17 ⁽¹⁾ | 40 | 50 | 60 | |
| | | 6 | | 34 | 43 | 51 | |
| t _{pd} | Propagation delay, MR to output | 2 | | 175 | 220 | 265 | ns |
| | | 4.5 | 12 ⁽¹⁾ | 35 | 44 | 53 | |
| | | 6 | | 30 | 37 | 45 | |
| t _{pd} | Propagation delay output enable to Q (Figure 6) | 2 | | 150 | 190 | 225 | ns |
| | | 4.5 | 12 ⁽¹⁾ | 30 | 38 | 45 | |
| | | 6 | | 26 | 33 | 38 | |
| t _t | Output transition times | 2 | | 60 | 75 | 90 | ns |
| | | 4.5 | | 12 | 15 | 18 | |
| | | 6 | | 10 | 13 | 15 | |
| f _{MAX} | Maximum clock frequency | 5 | 60 ⁽¹⁾ | | | | MHz |
| C _i | Input capacitance | | | 10 | 10 | 10 | pF |
| C _O | Three-state output capacitance | | | 10 | 10 | 10 | pF |
| C _{pd} (2) (3) | Power dissipation capacitance | 5 | 29 | | | | pF |
| HCT TYPES | | | | | | | |
| t _{pd} | Propagation delay, clock to output | 4.5 | 17 ⁽¹⁾ | 40 | 50 | 60 | ns |
| t _{pd} | Propagation delay, MR to output | 4.5 | 18 ⁽¹⁾ | 44 | 55 | 66 | ns |
| t _{pd} | Propagation delay output enable to Q (Figure 6) | 2 | | 150 | 190 | 225 | ns |
| | | 4.5 | 14 ⁽¹⁾ | 30 | 38 | 45 | |
| | | 6 | | 26 | 33 | 38 | |
| t _t | Output transition times | 4.5 | | 15 | 19 | 22 | ns |
| f _{MAX} | Maximum clock frequency | 5 | 60 ⁽¹⁾ | | | | MHz |
| C _i | Input capacitance | | | 10 | 10 | 10 | pF |
| C _{pd} (2) (3) | Power dissipation capacitance | 5 | 34 | | | | pF |

- (1) Typical value tested at 5V, C_L = 15pF.
- (2) C_{PD} is used to determine the dynamic power consumption, per package.
- (3) P_D = V_{CC}²f_i + Σ (C_L V_{CC}² + f_O) where f_i = Input Frequency, C_L = Output Load Capacitance, V_{CC} = Supply Voltage.


5.6 Prerequisite For Switching Characteristics

| PARAMETER | | V _{CC} (V) | 25°C | | -40°C to 85°C | | -55°C to 125°C | | UNITS |
|-------------------------------|---|---------------------|------|-----|---------------|-----|----------------|-----|-------|
| | | | MIN | MAX | MIN | MAX | MIN | MAX | |
| HC TYPES | | | | | | | | | |
| f _{MAX} | Maximum clock frequency | 2 | 6 | 5 | 4 | MHz | | | |
| | | 4.5 | 30 | 24 | 20 | | | | |
| | | 6 | 35 | 28 | 24 | | | | |
| t _W | MR pulse width | 2 | 80 | 100 | 120 | ns | | | |
| | | 4.5 | 16 | 20 | 24 | | | | |
| | | 6 | 14 | 17 | 20 | | | | |
| t _W | Clock pulse width | 2 | 80 | 100 | 120 | ns | | | |
| | | 4.5 | 16 | 20 | 24 | | | | |
| | | 6 | 14 | 17 | 20 | | | | |
| t _{SU} | Set-up time, data to clock and \bar{E} to clock | 2 | 60 | 75 | 90 | ns | | | |
| | | 4.5 | 12 | 15 | 18 | | | | |
| | | 6 | 10 | 13 | 15 | | | | |
| t _H | Hold time, data to clock | 2 | 3 | 3 | 3 | ns | | | |
| | | 4.5 | 3 | 3 | 3 | | | | |
| | | 6 | 3 | 3 | 3 | | | | |
| t _H | Hold time, \bar{E} to clock | 2 | 0 | 0 | 0 | ns | | | |
| | | 4.5 | 0 | 0 | 0 | | | | |
| | | 6 | 0 | 0 | 0 | | | | |
| t _{REM} | Removal time, MR to clock | 2 | 60 | 75 | 90 | ns | | | |
| | | 4.5 | 12 | 15 | 18 | | | | |
| | | 6 | 10 | 13 | 15 | | | | |
| HCT TYPES | | | | | | | | | |
| f _{MAX} | Maximum clock frequency | 4.5 | 20 | 16 | 13 | MHz | | | |
| t _W t _W | MR pulse width | 4.5 | 15 | 19 | 22 | ns | | | |
| t _W | Clock pulse width | 4.5 | 25 | 31 | 38 | ns | | | |
| t _{SU} | Set-up Time, \bar{E} to clock | 4.5 | 12 | 15 | 18 | ns | | | |
| t _{SU} | Set-up time, data to clock | 4.5 | 18 | 23 | 27 | ns | | | |
| t _H | Hold time, data to clock | 4.5 | 0 | 0 | 0 | ns | | | |
| t _H | Hold time, \bar{E} to clock | 4.5 | 0 | 0 | 0 | ns | | | |
| t _{REM} | Removal time, MR to clock | 4.5 | 12 | 15 | 18 | ns | | | |

6 Parameter Measurement Information


t_{PD} is the maximum between t_{PLH} and t_{PHL}

t_t is the maximum between t_{TLH} and t_{THL}



NOTE: Outputs should be switching from 10% V_{CC} to 90% V_{CC} in accordance with device truth table. For f_{MAX} , input duty cycle = 50%

Figure 6-1. HC clock pulse rise and fall times and pulse width



NOTE: Outputs should be switching from 10% V_{CC} to 90% V_{CC} in accordance with device truth table. For f_{MAX} , input duty cycle = 50%

Figure 6-2. HCT clock pulse rise and fall times and pulse width




Figure 6-3. HC and HCU transition times and propagation delay times, combination logic







Figure 6-4. HCT transition times and propagation delay times, combination logic




6-5. HC setup times, hold times, removal time, and propagation delay times for edge triggered sequential logic circuits




6-6. HCT setup times, hold times, removal time, and propagation delay times for edge triggered sequential logic circuits



6-7. HC three-state propagation delay waveform



6-8. HCT three-state propagation delay waveform



NOTE: Open drain waveforms t_{pLZ} and t_{pZL} are the same as those for three-state shown on the left. The test circuit is Output $R_L = 1k\Omega$ to V_{CC} , $C_L = 50pF$

6-9. HC and HCT three-state propagation delay test circuit

7 Detailed Description


7.1 Overview

The CDx4HC173 or CDx4HCT173 high speed three-state quad D-type flip-flops are fabricated with silicon gate CMOS technology. They possess the low power consumption of standard CMOS Integrated circuits, and can operate at speeds comparable to the equivalent low power Schottky devices. The buffered outputs can drive 15 LSTTL loads. The large output drive capability and three-state feature make these parts ideally suited for interfacing with bus lines in bus oriented systems

The four D-type flip-flops operate synchronously from a common clock. The outputs are in the three-state mode when either of the two output disable pins are at the logic “1” level. The input ENABLES allow the flip-flops to remain in their present states without having to disrupt the clock. If either of the 2 input ENABLES are taken to a logic “1” level, the Q outputs are fed back to the inputs, forcing the flip-flops to remain in the same state. Reset is enabled by taking the RESET (MR) input to a logic “1” level. The data outputs change state on the positive going edge of the clock.

The 'HCT173 logic family is functionally, as well as pin compatible with the standard LS logic family.

7.2 Functional Block Diagram



7.3 Device Functional Modes

表 7-1. Truth Table⁽¹⁾⁽²⁾

| INPUTS | | | | DATA D | OUTPUT Q _n |
|--------|----|-------------|----|-----------|--------------------------|
| MR | CP | DATA ENABLE | | | |
| | | E1 | E2 | | |
| H | X | X | X | X | L |
| L | L | X | X | X | Q ₀ |
| L | ↑ | H | X | X | Q ₀ |
| L | ↑ | X | H | X | Q ₀ |
| L | ↑ | L | L | L | L |
| L | ↑ | L | L | H | H |

- (1) H = High voltage level. L = Low voltage level. X = Irrelevant. ↑ = Transition from low to high level. Q₀ = Level before the indicated steady-state input conditions were established.
- (2) When either OE1 or OE2 (or both) is (are) high, the output is disabled to the high-impedance stat, however, sequential operation of the flip-flops is not affected.

8 Power Supply Recommendations

The power supply can be any voltage between the minimum and maximum supply voltage rating located in the *Recommended Operating Conditions*. Each V_{CC} terminal should have a good bypass capacitor to prevent power disturbance. A 0.1- μF capacitor is recommended for this device. It is acceptable to parallel multiple bypass caps to reject different frequencies of noise. The 0.1- μF and 1- μF capacitors are commonly used in parallel. The bypass capacitor should be installed as close to the power terminal as possible for best results.

9 Layout

9.1 Layout Guidelines

When using multiple-input and multiple-channel logic devices inputs must not ever be left floating. In many cases, functions or parts of functions of digital logic devices are unused; for example, when only two inputs of a triple-input AND gate are used or only 3 of the 4 buffer gates are used. Such unused input pins must not be left unconnected because the undefined voltages at the outside connections result in undefined operational states. All unused inputs of digital logic devices must be connected to a logic high or logic low voltage, as defined by the input voltage specifications, to prevent them from floating. The logic level that must be applied to any particular unused input depends on the function of the device. Generally, the inputs are tied to GND or V_{CC} , whichever makes more sense for the logic function or is more convenient.

10 Device and Documentation Support

TI offers an extensive line of development tools. Tools and software to evaluate the performance of the device, generate code, and develop solutions are listed below.

10.1 Documentation Support

10.1.1 Related Documentation

10.2 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on [ti.com](https://www.ti.com). Click on *Subscribe to updates* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

10.3 サポート・リソース

TI E2E™ サポート・フォーラムは、エンジニアが検証済みの回答と設計に関するヒントをエキスパートから迅速かつ直接得ることができる場所です。既存の回答を検索したり、独自の質問をしたりすることで、設計に必要な支援を迅速に得ることができます。

リンクされているコンテンツは、該当する貢献者により、現状のまま提供されるものです。これらは TI の仕様を構成するものではなく、必ずしも TI の見解を反映したものではありません。TI の [使用条件](#) を参照してください。

10.4 Trademarks

TI E2E™ is a trademark of Texas Instruments.

すべての商標は、それぞれの所有者に帰属します。

10.5 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

10.6 Glossary

[TI Glossary](#) This glossary lists and explains terms, acronyms, and definitions.

11 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

PACKAGING INFORMATION

| Orderable Device | Status (1) | Package Type | Package Drawing | Pins | Package Qty | Eco Plan (2) | Lead finish/ Ball material (6) | MSL Peak Temp (3) | Op Temp (°C) | Device Marking (4/5) | Samples |
|------------------|---------------|--------------|-----------------|------|-------------|------------------|--------------------------------------|----------------------|--------------|---------------------------------|-------------------------|
| 5962-8682501EA | ACTIVE | CDIP | J | 16 | 25 | Non-RoHS & Green | SNPB | N / A for Pkg Type | -55 to 125 | 5962-8682501EA CD54HC173F3A | Samples |
| 5962-8875901EA | ACTIVE | CDIP | J | 16 | 25 | Non-RoHS & Green | SNPB | N / A for Pkg Type | -55 to 125 | 5962-8875901EA CD54HCT173F3A | Samples |
| CD54HC173F | ACTIVE | CDIP | J | 16 | 25 | Non-RoHS & Green | SNPB | N / A for Pkg Type | -55 to 125 | CD54HC173F | Samples |
| CD54HC173F3A | ACTIVE | CDIP | J | 16 | 25 | Non-RoHS & Green | SNPB | N / A for Pkg Type | -55 to 125 | 5962-8682501EA CD54HC173F3A | Samples |
| CD54HCT173F3A | ACTIVE | CDIP | J | 16 | 25 | Non-RoHS & Green | SNPB | N / A for Pkg Type | -55 to 125 | 5962-8875901EA CD54HCT173F3A | Samples |
| CD74HC173E | ACTIVE | PDIP | N | 16 | 25 | RoHS & Green | NIPDAU | N / A for Pkg Type | -55 to 125 | CD74HC173E | Samples |
| CD74HC173M | OBSOLETE | SOIC | D | 16 | | TBD | Call TI | Call TI | -55 to 125 | HC173M | |
| CD74HC173M96 | ACTIVE | SOIC | D | 16 | 2500 | RoHS & Green | NIPDAU | Level-1-260C-UNLIM | -55 to 125 | HC173M | Samples |
| CD74HC173PW | OBSOLETE | TSSOP | PW | 16 | | TBD | Call TI | Call TI | -55 to 125 | HJ173 | |
| CD74HC173PWR | ACTIVE | TSSOP | PW | 16 | 2000 | RoHS & Green | NIPDAU SN | Level-1-260C-UNLIM | -55 to 125 | HJ173 | Samples |
| CD74HCT173E | ACTIVE | PDIP | N | 16 | 25 | RoHS & Green | NIPDAU | N / A for Pkg Type | -55 to 125 | CD74HCT173E | Samples |
| CD74HCT173M | OBSOLETE | SOIC | D | 16 | | TBD | Call TI | Call TI | -55 to 125 | HCT173M | |
| CD74HCT173M96 | ACTIVE | SOIC | D | 16 | 2500 | RoHS & Green | NIPDAU | Level-1-260C-UNLIM | -55 to 125 | HCT173M | Samples |

(1) The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

RoHS Exempt: TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

Green: TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of ≤ 1000 ppm threshold. Antimony trioxide based flame retardants must also meet the ≤ 1000 ppm threshold requirement.

- (3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.
- (4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.
- (5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.
- (6) Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

OTHER QUALIFIED VERSIONS OF CD54HC173, CD54HCT173, CD74HC173, CD74HCT173 :

- Catalog : [CD74HC173](#), [CD74HCT173](#)
- Military : [CD54HC173](#), [CD54HCT173](#)

NOTE: Qualified Version Definitions:

- Catalog - TI's standard catalog product
- Military - QML certified for Military and Defense Applications

TAPE AND REEL INFORMATION



QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|---------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| CD74HC173M96 | SOIC | D | 16 | 2500 | 330.0 | 16.4 | 6.5 | 10.3 | 2.1 | 8.0 | 16.0 | Q1 |
| CD74HC173PWR | TSSOP | PW | 16 | 2000 | 330.0 | 12.4 | 6.9 | 5.6 | 1.6 | 8.0 | 12.0 | Q1 |
| CD74HC173PWR | TSSOP | PW | 16 | 2000 | 330.0 | 12.4 | 6.85 | 5.45 | 1.6 | 8.0 | 12.0 | Q1 |
| CD74HC173PWR | TSSOP | PW | 16 | 2000 | 330.0 | 12.4 | 6.9 | 5.6 | 1.6 | 8.0 | 12.0 | Q1 |
| CD74HCT173M96 | SOIC | D | 16 | 2500 | 330.0 | 16.4 | 6.5 | 10.3 | 2.1 | 8.0 | 16.0 | Q1 |

TAPE AND REEL BOX DIMENSIONS



*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Length (mm) | Width (mm) | Height (mm) |
|---------------|--------------|-----------------|------|------|-------------|------------|-------------|
| CD74HC173M96 | SOIC | D | 16 | 2500 | 353.0 | 353.0 | 32.0 |
| CD74HC173PWR | TSSOP | PW | 16 | 2000 | 356.0 | 356.0 | 35.0 |
| CD74HC173PWR | TSSOP | PW | 16 | 2000 | 366.0 | 364.0 | 50.0 |
| CD74HC173PWR | TSSOP | PW | 16 | 2000 | 356.0 | 356.0 | 35.0 |
| CD74HCT173M96 | SOIC | D | 16 | 2500 | 340.5 | 336.1 | 32.0 |

TUBE


*All dimensions are nominal

| Device | Package Name | Package Type | Pins | SPQ | L (mm) | W (mm) | T (μm) | B (mm) |
|-------------|--------------|--------------|------|-----|--------|--------|--------|--------|
| CD74HC173E | N | PDIP | 16 | 25 | 506 | 13.97 | 11230 | 4.32 |
| CD74HC173E | N | PDIP | 16 | 25 | 506 | 13.97 | 11230 | 4.32 |
| CD74HCT173E | N | PDIP | 16 | 25 | 506 | 13.97 | 11230 | 4.32 |
| CD74HCT173E | N | PDIP | 16 | 25 | 506 | 13.97 | 11230 | 4.32 |

D (R-PDSO-G16)

PLASTIC SMALL OUTLINE



4040047-6/M 06/11

- NOTES:
- A. All linear dimensions are in inches (millimeters).
 - B. This drawing is subject to change without notice.
 -  C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.006 (0,15) each side.
 -  D. Body width does not include interlead flash. Interlead flash shall not exceed 0.017 (0,43) each side.
 - E. Reference JEDEC MS-012 variation AC.



4220204/A 02/2017

NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-153.

EXAMPLE BOARD LAYOUT

PW0016A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE
EXPOSED METAL SHOWN
SCALE: 10X



SOLDER MASK DETAILS

4220204/A 02/2017

NOTES: (continued)

- 6. Publication IPC-7351 may have alternate designs.
- 7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

EXAMPLE STENCIL DESIGN

PW0016A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



SOLDER PASTE EXAMPLE
BASED ON 0.125 mm THICK STENCIL
SCALE: 10X

4220204/A 02/2017

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

J (R-GDIP-T**)

14 LEADS SHOWN

CERAMIC DUAL IN-LINE PACKAGE



| DIM \ PINS ** | 14 | 16 | 18 | 20 |
|---------------|------------------------|------------------------|------------------------|------------------------|
| A | 0.300 (7,62) BSC | 0.300 (7,62) BSC | 0.300 (7,62) BSC | 0.300 (7,62) BSC |
| B MAX | 0.785 (19,94) | .840 (21,34) | 0.960 (24,38) | 1.060 (26,92) |
| B MIN | — | — | — | — |
| C MAX | 0.300 (7,62) | 0.300 (7,62) | 0.310 (7,87) | 0.300 (7,62) |
| C MIN | 0.245 (6,22) | 0.245 (6,22) | 0.220 (5,59) | 0.245 (6,22) |



4040083/F 03/03

- NOTES:
- All linear dimensions are in inches (millimeters).
 - This drawing is subject to change without notice.
 - This package is hermetically sealed with a ceramic lid using glass frit.
 - Index point is provided on cap for terminal identification only on press ceramic glass frit seal only.
 - Falls within MIL STD 1835 GDIP1-T14, GDIP1-T16, GDIP1-T18 and GDIP1-T20.

N (R-PDIP-T**)

PLASTIC DUAL-IN-LINE PACKAGE

16 PINS SHOWN



- NOTES:
- A. All linear dimensions are in inches (millimeters).
 - B. This drawing is subject to change without notice.
 - C Falls within JEDEC MS-001, except 18 and 20 pin minimum body length (Dim A).
 - D The 20 pin end lead shoulder width is a vendor option, either half or full width.

4040049/E 12/2002

重要なお知らせと免責事項

TI は、技術データと信頼性データ(データシートを含みます)、設計リソース(リファレンス・デザインを含みます)、アプリケーションや設計に関する各種アドバイス、Web ツール、安全性情報、その他のリソースを、欠陥が存在する可能性のある「現状のまま」提供しており、商品性および特定目的に対する適合性の黙示保証、第三者の知的財産権の非侵害保証を含むいかなる保証も、明示的または黙示的にかかわらず拒否します。

これらのリソースは、TI 製品を使用する設計の経験を積んだ開発者への提供を意図したものです。(1) お客様のアプリケーションに適した TI 製品の選定、(2) お客様のアプリケーションの設計、検証、試験、(3) お客様のアプリケーションに該当する各種規格や、その他のあらゆる安全性、セキュリティ、規制、または他の要件への確実な適合に関する責任を、お客様のみが単独で負うものとし、

上記の各種リソースは、予告なく変更される可能性があります。これらのリソースは、リソースで説明されている TI 製品を使用するアプリケーションの開発の目的でのみ、TI はその使用をお客様に許諾します。これらのリソースに関して、他の目的で複製することや掲載することは禁止されています。TI や第三者の知的財産権のライセンスが付与されている訳ではありません。お客様は、これらのリソースを自身で使用した結果発生するあらゆる申し立て、損害、費用、損失、責任について、TI およびその代理人を完全に補償するものとし、TI は一切の責任を拒否します。

TI の製品は、[TI の販売条件](#)、または [ti.com](#) やかかる TI 製品の関連資料などのいずれかを通じて提供する適用可能な条項の下で提供されています。TI がこれらのリソースを提供することは、適用される TI の保証または他の保証の放棄の拡大や変更を意味するものではありません。

お客様がいかなる追加条項または代替条項を提案した場合でも、TI はそれらに異議を唱え、拒否します。

郵送先住所 : Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2024, Texas Instruments Incorporated