




TEXAS INSTRUMENTS
 ADS42LB49/69EVM REV D
 SOME GREEN STOP LYR 1




TEXAS INSTRUMENTS
ADS42LB49/69EVM REV D
LAYER 2 (GND1)




TEXAS INSTRUMENTS
ADS42LB49/69EVM REV D
LAYER 3 (PWR1)



TEXAS INSTRUMENTS
ADS42LB49/69EVM REV D
LAYER 4 (PWR2)



TEXAS INSTRUMENTS
ADS42LB49/69EVM REV D
LAYER 5 (GND2)



TEXAS INSTRUMENTS
ADS42LB49/69EVM REV D
SIDE SCREEN BOTTOM



UNLESS OTHERWISE SPECIFIED, ALL NOTES ARE APPLICABLE.
 NOTES PRECEDED BY AN UNMARKED "□" ARE NOT APPLICABLE.

ZONE		REVISIONS	
LTR	DESCRIPTION	DATE	APPROVED

1. APPLICATION DESIGN MANUFACTURING AND INSPECTION DOCUMENTS, IPC-2221A & IPC-2222 / DESIGN STANDARD FOR RIGID PRINTED CIRCUIT BOARDS AND RIGID PRINTED BOARD ASSEMBLIES, IPC-2018B / QUALIFICATION AND PERFORMANCE SPECIFICATION FOR RIGID PRINTED BOARD, IPC-A-600G / ACCEPTABILITY OF PRINTED BOARDS.
2. HOLE SIZE APPLIES AFTER PLATING, TOLERANCE TO BE +/- .003.
3. REGISTRATION TOLERANCE; ARTWORK +/- .002 ALL HOLE CENTERS +/- .005 FROM DIMENSION DATUM.
4. MINIMUM COPPER WALL THICKNESS SHALL BE .001 INCH. FOR ALL PLATED THROUGH HOLES. BREAKOUT NOT ALLOWED.
5. PROCESS AND MATERIAL MUST CONFORM TO UL 794. MATERIAL MUST MEET OR EXCEED UL FLAMMABILITY RATING 94V-0. MATERIAL: SINGLE SIDED, DOUBLE SIDED, MULTI-LAYER (SEE DETAIL "A") SEE LAYER STACKUP FOR ALL PRE-PREG & CORE THICKNESSES, COPPER OZ AND MATERIAL. FINISHED BOARD THICKNESS: .062 +/- .010.
6. MANUFACTURE'S UL MARKING, FLAMMABILITY RATING, LOGO AND DATE CODE TO BE PLACED IN SILKSCREEN ON BOTTOM SIDE OF THE BOARD.
7. SOLDERMASK BOTH SIDES USING TAIYO (OR EQUIVALENT). COLOR-RED (0.001 TO 0.002" THICK OVER METAL).
8. SILKSCREEN TOP SIDE BOTH SIDES, USING YELLOW WHITE NPI LEADFREE. REGISTRATION TOLERANCE TO BE +/- .005. INK IS NOT ALLOWED ON EXPOSED PLATED AREA.
9. P.C. BOARD TO BE FREE OF DIRT, OIL, FINGER PRINTS, ETC.
10. BOARD WARPAGE; WARP AND TWIST SHALL NOT EXCEED .007 INCH PER INCH. MEASURED AT ANY LOCATION OR DIRECTION ON THE BOARD.
11. BOARD MUST BE 100% ELECTRICALLY TESTED TO ENSURE NO SHORTS OR OPEN CIRCUITS AT 20V.
12. ALL INNER LAYER UNCONNECTED PADS SHALL BE REMOVED.

13. OUTER LAYERS USING A 19.5 mil TRACE WIDTH SHALL BE 50ohms SINGLE ENDED, +/- 10% TOLERANCE. OUTER LAYERS USING A 8.5 mil TRACE WIDTH AND 6.5 mil SPACING SHALL BE 100 ohms DIFFERENTIAL, +/- 10% TOLERANCE.
14. MINIMUM COPPER CONDUCTOR WIDTH IS: 6 MIL. MINIMUM COPPER SPACING IS: 5 MIL.
15. SMOBC/IMMERSION GOLD: 3-8 uIN OVER 100-200 uIN NICKEL PLATING.
16. GROUND ETCH TO BOARD EDGE IS INTENTIONAL. DO NOT PULL BACK.
17. NO CHANGES TO ANY ARTWORK ARE PERMITTED WITHOUT WRITTEN AUTHORIZATION.
18. FINISHED BOARD MUST BE ROHS COMPLIANT AND SURVIVE A LEAD FREE ASSEMBLY. MAXIMUM REFLOW OF 260 DEGREES C (6 PASSES).
19. HOLE SIZE APPLIES AFTER PLATING. TOLERANCE TO BE +/- .003/- .010.

DETAIL "A"



DRILL CHART: TOP to BOTTOM			
ALL UNITS ARE IN MILS			
FIGURE	SIZE	PLATED	QTY
-	10.0	PLATED	1359
•	12.01	PLATED	50
•	38.0	PLATED	10
•	40.0	PLATED	5
•	53.0	PLATED	5
•	62.0	PLATED	2
•	68.0	PLATED	2
A	250.0	PLATED	2
•	18.0	NON-PLATED	2
•	40.0	NON-PLATED	2
D	125.0	NON-PLATED	4

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. FRACTIONS DECIMALS ANGLES +/- .XXX +/- .005 +/- .01 +/- .005 +/- .01 +/- .005	CONTRACT NO.	TEXAS INSTRUMENTS INC.	
	APPROVALS	DATE	FABRICATION DRAWING AD542LB49/69EVM
DRAWN L. NGUYEN	03-19-12		
MATERIAL SEE NOTE 5	ENGR M. GUIBOND		
FINISH SEE NOTES 7, 8, 9		SIZE B CODE IDENT NO. DRAWING NO.	REV. D
DO NOT SCALE DRAWING		SCALE NONE	SHEET 1 OF 1