Layer	Name	Material	Thickness	Constant	Board Layer Stack	Board Layer Stack
1	Top Overlay					
2	Top Solder	Solder Resist	0.40mil	3.5		
3	Top Layer	Copper	1.40mil			
4	Dielectric1	FR-4 High Tg	59.20mil	4.8		
5	Bottom Layer	Copper	1.40mil			
6	Bottom Solder	Solder Resist	0.40mil	3.5		
7	Bottom Overlay					

Symbol	Count	Hole Size	Plated	Hole Type	Hole Length
⌖	46	7.87mil (0.200mm)	PTH	Round	-
○	74	12.00mil (0.305mm)	PTH	Round	-
▽	4	29.53mil (0.750mm)	PTH	Round	-
□	18	40.00mil (1.016mm)	PTH	Round	-
☼	6	43.31mil (1.100mm)	PTH	Round	-
⌘	4	157.00mil (3.988mm)	NPTH	Round	-
	152 Total				

Drill Table

FOR 7.874MIL DRILL +0/-7.874MIL
FOR 12MIL DRILL +0/-12MIL
FOR 16MIL DRILL +0/-16MIL
FOR PTH DRILL +/-3MIL
FOR NPTH DRILL +/-2MIL





DESIGN INFORMATION

BOARD SIZE (REFER ALSO ARRAY/PANEL PROFILING INFORMATION)
95MM X 35MM

Number of Layers : 2
MIN. TRACK WIDTH: 8 MIL
MIN. CLEARANCE: 7.7 MIL
MIN. VIA DRILL SIZE: 7.874 MIL

MINIMUM ANNULAR RING 6 MIL (0.1524 mm) EXTERNAL
PER IPC-D-275 CLASS 2 LEVEL C
REGISTRATION TOLERANCES: METAL +/- 5 MIL, HOLES +/- 3 MIL

MATERIAL:
[ ] FR-408 [X] FR-4 High Tg [ ] OTHER
THICKNESS: [X] 63 MIL (1.6mm) +/-10% [ ] OTHER
TOLERANCE: [X] ANSI IPC-6012 TYPE 3 CLASS 2
[ ] OTHER +/-
BOW & TWIST: [X] ANSI IPC-6012 TYPE 3 CLASS 2
[ ] OTHER +/-
COPPER THICKNESS (FINISHED):
OUTER: [X] 1.4MIL (1oz) [ ] 2MIL (1.4oz) [ ] 2.8MIL (2oz)
INNER SIGNAL: [ ] 1.4MIL (1oz) [ ] 2.8MIL (2oz) [X] N/A
DRILLING:
REFERENCE: [X] AS SHOWN [X] NC_DRILL FILES
PTH MIN COPPER THICKNESS: [X] 1MIL [ ] OTHER
BOARD FINISH:
SILKSCREEN: [X] TOP [X] BOTTOM
SILKSCREEN COLOR: [X] WHITE [ ] OTHER
SOLDER RESIST COLOR:
[X] GREEN [ ] BLUE [ ] OTHER
SURFACE FINISH: [X] IMMERSION GOLD (ENIG) [ ] ENEPIG
[ ] IMM. TIN/SILVER OR EQUIV [ ] OTHER
ARRAY/PANEL: [ ] CUT AND TRIM PER MECH LAYER 1
[ ] N.C. ROUTE [X] V. SCORE
CERTIFICATION: MATERIALS AND WORKMANSHIP FOR ALL PCBS TO MEET OR EXCEED THE REQUIREMENTS OF:
[X] ANSI IPC-A-600F CLASS -> [ ] 1 [X] 2 [ ] 3
[X] UL 94V-0 [X] RoHS [ ] OTHER PER ORDER
ADDITIONAL REQUIREMENTS: VIA TENTING: YES [ ] NO [X]
MICROSECTION: [ ] YES IMPEDANCE CONTROL: YES [ ] NO [X]
BARE BOARD ELEC. TEST: [ ] NONE [X] REQUIRED [ ] PER ORDER
MANUFACTURER'S UL: [ ] RAIL [ ] METAL [X] SILK

TEXAS INSTRUMENTS

PROJECT TITLE: TIDA-010008_DCinput_Protection
DESIGNED FOR: Public Release
FILE NAME: TIDA-010008_DCinput_Protection.PcbDoc

ENGINEER: Sreenivasa	LAYOUT BY: Avinash N
SCALE: 1.00	ALTIUM DESIGNER VERSION: 18.1.9.240

ALL ARTWORK VIEWED FROM TOP SIDE	BOARD #: TIDA-010008_DCinput_Protection REV: E1	SVN REV: Not In VersionControl
LAYER NAME = Drill Drawing	TID #: 010008	
PLOT NAME = Fabrication Drawing	GENERATED : 5/24/2019 11:05:19 AM	TEXAS INSTRUMENTS

Texas Instruments (TI) and/or its licensors do not warrant the accuracy or completeness of this specification or any information contained therein. TI and/or its licensors do not warrant that this design will meet the specifications, will be suitable for your application or fit for any particular purpose, or will operate in an implementation. TI and/or its licensors do not warrant that the design is production worthy. You should completely validate and test your design implementation to confirm the system functionality for your application.