


Automotive Sepic

- Input 4.0 .. 13.0V
- Output 11.0V @ 0.3A
- Free-Running-Switching Frequency of 400 kHz



1. Startup

The startup waveform at 13.0V input voltage and no load on the 11.0V output is shown in Figure 1.

Channel C1 **13.0V Input Voltage**

2V/div, 20ms/div

Channel C2 **11.0V Output Voltage**

2V/div, 20ms/div




Figure 1

2. Shutdown

The shutdown waveform at 13.0V input voltage and 0.3A load at 11.0V output voltage is shown in Figure 2.

Channel C1 **13.0V Input Voltage**
2V/div, 1ms/div

Channel C2 **11.0V Output Voltage**
2V/div, 1ms/div




Figure 2

3. Efficiency

The efficiency and load regulation are shown in Figure 3 and Figure 4.




Figure 3




Figure 4

4. Transient Response

The response to a load step at 11.0V output voltage is shown in Figure 5.

Channel C1 **Output Current**, Load Step 0.15A to 0.3A
100mA/div, 1ms/div

Channel C2 **Output Voltage**, -232mV undershoot (2.1%), 268mV overshoot (2.4%)
200mV/div, 1ms/div, AC coupled




Figure 5

5. Frequency Response

The frequency response is shown in Figure 6.

4.0V Input, 0.3A Load	0.6 kHz Bandwidth, 66 deg Phase Margin, -29 dB Gain Margin
7.0V Input, 0.3A Load	1.8 kHz Bandwidth, 59 deg Phase Margin, -19 dB Gain Margin
13.0V Input, 0.3A Load	2.8 kHz Bandwidth, 59 deg Phase Margin, -23 dB Gain Margin




Figure 6

6. Input Ripple

The input ripple is shown in Figure 7.

Channel M1 **Input Voltage @ 4.0V Input / 0.3A Load**

100mV/div, 1us/div

Channel M2 **Input Voltage @ 7.0V Input / 0.3A Load**

100mV/div, 1us/div

Channel M3 **Input Voltage @ 13.0V Input / 0.3A Load**

100mV/div, 1us/div




Figure 7

7. Output Ripple

The output ripple voltage is shown in Figure 8.

Channel M1 **Output Voltage @ 4.0V Input / 0.3A Load**

200mV/div, 1us/div

Channel M2 **Output Voltage @ 7.0V Input / 0.3A Load**

200mV/div, 1us/div

Channel M3 **Output Voltage @ 13.0V Input / 0.3A Load**

200mV/div, 1us/div




Figure 8

8. Low-Side FET (Switching Node)

The drain-source voltage of the low-side FET at 13.0V input voltage and 0.3A load on the output is shown in Figure 9.

Channel C1 **Drain-Source Voltage**, -0.8V minimum, 25.1V maximum
5V/div, 1us/div




Figure 9

10. Diode Voltage

The voltage of the diode at 13.0V input voltage and 0.3A load on the output is shown in Figure 10.

Channel C1 **Drain-Source Voltage**, -1.3V minimum, 24.9V maximum
5V/div, 1us/div




Figure 10

11. Thermal Image

The thermal image (Figure 11) shows the circuit at an ambient temperature of 20°C with an input voltage of 13.0V and 0.3A load on the output.




Figure 11

Name	Temperature	Emissivity	Background
L1	40.3°C	0.95	20.0°C
D1	35.4°C	0.95	20.0°C
U1	35.4°C	0.95	20.0°C

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale (<https://www.ti.com/legal/termsofsale.html>) or other applicable terms available either on [ti.com](https://www.ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2021, Texas Instruments Incorporated