



UNLESS OTHERWISE SPECIFIED, ALL NOTES ARE APPLICABLE.  
 NOTES PRECEDED BY AN UNMARKED "□" ARE NOT APPLICABLE.

1. APPLICATION DESIGN MANUFACTURING AND INSPECTION DOCUMENTS.  
 IPC-2221A & IPC-2222 / DESIGN STANDARD FOR RIGID PRINTED CIRCUIT BOARDS AND RIGID PRINTED BOARD ASSEMBLIES.  
 IPC-6012B / QUALIFICATION AND PERFORMANCE SPECIFICATION FOR RIGID PRINTED BOARD.  
 IPC-A-600G / ACCEPTABILITY OF PRINTED BOARDS.
2. HOLE SIZE APPLY AFTER PLATING. TOLERANCE TO BE +/- .003.
3. REGISTRATION TOLERANCE: ARTWORK +/- .002  
 ALL HOLE CENTERS +/- .005 FROM DIMENSION DATUM.
4. MINIMUM COPPER WALL THICKNESS SHALL BE .001 INCH.  
 FOR ALL PLATED THROUGH HOLES. BREAKOUT NOT ALLOWED.
5. PROCESS AND MATERIAL MUST CONFORM TO UL 796. MATERIAL MUST MEET OR EXCEED UL FLAMMABILITY RATING 94V-0.  
 MATERIAL:  SINGLE SIDED,  DOUBLE SIDED,  MULTI-LAYER (SEE DETAIL "A")  
 SEE LAYER STACKUP FOR ALL PRE-PREG & CORE THICKNESSES, COPPER OZ AND MATERIAL. FINISHED BOARD THICKNESS: .063 +/- 10%
6. MANUFACTURE'S UL MARKING, FLAMMABILITY RATING, LOGO AND DATE CODE TO BE PLACED IN SILKSCREEN ON BOTTOM SIDE OF THE BOARD.
7. SOLDERMASK BOTH SIDES USING TAIYO (OR EQUIVALENT).  
 COLOR-RED (0.001 TO 0.002" THICK OVER METAL).
8. SILKSCREEN  TOP SIDE  BOTH SIDES, USING  YELLOW  WHITE NPI LEADFREE.  
 REGISTRATION TOLERANCE TO BE +/- .005. INK IS NOT ALLOWED ON EXPOSED PLATED AREA.
9. P.C. BOARD TO BE FREE OF DIRT, OIL, FINGER PRINTS, ETC.
10. BOARD WARPAGE: WARP AND TWIST SHALL NOT EXCEED .007 INCH PER INCH.  
 MEASURED AT ANY LOCATION OR DIRECTION ON THE BOARD.
11. BOARD MUST BE 100% ELECTRICALLY TESTED TO ENSURE NO SHORTS OR OPEN CIRCUITS AT 20V.
12.  ALL OUTER LAYERS USING A 6.0 mil TRACE WIDTH AND 4.5 mil SPACING SHALL BE 100 ohms DIFFERENTIAL, +/- 10% TOLERANCE.
13. MINIMUM COPPER CONDUCTOR WIDTH IS: 6MIL.  
 MINIMUM COPPER SPACING IS: 4.5MIL.
14. SMOBC/IMMERSION GOLD: 3-8 uIN OVER 100-200 uIN NICKEL PLATING.
15. NO CHANGES TO ANY ARTWORK ARE PERMITTED WITHOUT WRITTEN AUTHORIZATION.
- HOLE SIZE APPLIES AFTER PLATING. TOLERANCE TO BE +/- .003/- .010.



DRILL CHART: TOP to BOTTOM			
ALL UNITS ARE IN MILS			
FIGURE	SIZE	PLATED	QTY
.	10.0	PLATED	300 <input checked="" type="checkbox"/>
*	40.0	NON-PLATED	2
*	41.0	NON-PLATED	2
Y	125.0	NON-PLATED	6



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: FRACTIONS DECIMALS ANGLES +/- .XX +/- .01 +/- +/- .XXX +/- .005 +/-	CONTRACT NO.		TEXAS INSTRUMENTS INC.	
	APPROVALS	DATE	FABRICATION DRAWING HSMC-ADC-BRIDGE	
DRAWN P. LARSON	09-16-09	ENGR R. PRENTICE		
MATERIAL SEE NOTE 5			SIZE B	CODE IDENT NO. DRAWING NO. REV. 
FINISH SEE NOTES 7, 8, 9			SCALE NONE	SHEET 1 OF 1
DO NOT SCALE DRAWING				