

TAPE AND REEL INFORMATION

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE


*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
ISO7741FTADWRQ1	SOIC	DW	16	2000	330.0	16.4	10.75	10.7	2.7	12.0	16.0	Q1
ISO7741FTBDWRQ1	SOIC	DW	16	2000	330.0	16.4	10.75	10.7	2.7	12.0	16.0	Q1
ISO7741TADWRQ1	SOIC	DW	16	2000	330.0	16.4	10.75	10.7	2.7	12.0	16.0	Q1
ISO7741TBDWRQ1	SOIC	DW	16	2000	330.0	16.4	10.75	10.7	2.7	12.0	16.0	Q1
ISO7742FTADWRQ1	SOIC	DW	16	2000	330.0	16.4	10.75	10.7	2.7	12.0	16.0	Q1
ISO7742FTBDWRQ1	SOIC	DW	16	2000	330.0	16.4	10.75	10.7	2.7	12.0	16.0	Q1
ISO7742TADWRQ1	SOIC	DW	16	2000	330.0	16.4	10.75	10.7	2.7	12.0	16.0	Q1
ISO7742TBDWRQ1	SOIC	DW	16	2000	330.0	16.4	10.75	10.7	2.7	12.0	16.0	Q1

TAPE AND REEL BOX DIMENSIONS


*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
ISO7741FTADWRQ1	SOIC	DW	16	2000	367.0	367.0	45.0
ISO7741FTBDWRQ1	SOIC	DW	16	2000	367.0	367.0	45.0
ISO7741TADWRQ1	SOIC	DW	16	2000	367.0	367.0	45.0
ISO7741TBDWRQ1	SOIC	DW	16	2000	367.0	367.0	45.0
ISO7742FTADWRQ1	SOIC	DW	16	2000	367.0	367.0	45.0
ISO7742FTBDWRQ1	SOIC	DW	16	2000	367.0	367.0	45.0
ISO7742TADWRQ1	SOIC	DW	16	2000	367.0	367.0	45.0
ISO7742TBDWRQ1	SOIC	DW	16	2000	367.0	367.0	45.0