

TAPE AND REEL INFORMATION

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE


*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
LMR51625XDDCR	SOT-23-THIN	DDC	6	3000	180.0	8.4	3.2	3.2	1.4	4.0	8.0	Q3
LMR51625XFDDCR	SOT-23-THIN	DDC	6	3000	180.0	8.4	3.2	3.2	1.4	4.0	8.0	Q3
LMR51625YDDCR	SOT-23-THIN	DDC	6	3000	180.0	8.4	3.2	3.2	1.4	4.0	8.0	Q3
LMR51625YFDDCR	SOT-23-THIN	DDC	6	3000	180.0	8.4	3.2	3.2	1.4	4.0	8.0	Q3
LMR51635XDDCR	SOT-23-THIN	DDC	6	3000	180.0	8.4	3.2	3.2	1.4	4.0	8.0	Q3
LMR51635XFDDCR	SOT-23-THIN	DDC	6	3000	180.0	8.4	3.2	3.2	1.4	4.0	8.0	Q3
LMR51635YDDCR	SOT-23-THIN	DDC	6	3000	180.0	8.4	3.2	3.2	1.4	4.0	8.0	Q3
LMR51635YFDDCR	SOT-23-THIN	DDC	6	3000	180.0	8.4	3.2	3.2	1.4	4.0	8.0	Q3

TAPE AND REEL BOX DIMENSIONS


*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
LMR51625XDDCR	SOT-23-THIN	DDC	6	3000	210.0	185.0	35.0
LMR51625XFDDCR	SOT-23-THIN	DDC	6	3000	210.0	185.0	35.0
LMR51625YDDCR	SOT-23-THIN	DDC	6	3000	210.0	185.0	35.0
LMR51625YFDDCR	SOT-23-THIN	DDC	6	3000	210.0	185.0	35.0
LMR51635XDDCR	SOT-23-THIN	DDC	6	3000	210.0	185.0	35.0
LMR51635XFDDCR	SOT-23-THIN	DDC	6	3000	210.0	185.0	35.0
LMR51635YDDCR	SOT-23-THIN	DDC	6	3000	210.0	185.0	35.0
LMR51635YFDDCR	SOT-23-THIN	DDC	6	3000	210.0	185.0	35.0